

GC - CuSn7Pb (Rg 7)


Neue Werkstoffbezeichnung: CC 493 K (2.1090) Lagerlängen ab 1000mm

	GC - CuSn7Pb (Rg7) CC 493 K W.-Nr. 2.1090	
Abmessung Ø [mm] Liefermaße	Abmessung Ø [mm] Liefermaße	
26 x (14 / 17)	61 x (19 / 24 / 29 / 34 / 39 / 44 / 49)	122 x (48 / 58 / 68 / 78 / 88 / 98)
29 x 19	66 x (29 / 34 / 39 / 44 / 49 / 54)	132 x (48 / 58 / 68 / 78 / 88 / 98)
31 x (14 / 18)	71 x (18 / 28 / 33 / 38 / 43 / 48 / 53 / 58)	142 x (58 / 68 / 78 / 88 / 98)
33 x (19 / 23)	76 x (28 / 38 / 43 / 48 / 53 / 58)	152 x (58 / 68 / 78 / 88 / 98 / 108 / 118)
36 x (14 / 24)	82 x (28 / 38 / 48 / 58 / 63)	163 x (97 / 117 / 127)
37 x 17	83 x 68	173 x (107 / 127 / 137)
39 x (26 / 28)	87 x (38 / 58 / 63 / 68)	183 x (117 / 127 / 147)
41 x (14 / 19 / 24 / 29)	92 x (28 / 38 / 48 / 58 / 68 / 73)	193 x (107 / 127 / 147)
46 x (14 / 19 / 24 / 29 / 34)	97 x (48 / 58 / 68 / 73)	
51 x (14 / 19 / 24 / 29 / 34 / 39)	102 x (28 / 38 / 48 / 58 / 68 / 78)	
56 x (19 / 24 / 29 / 34 / 39 / 44)	112 x (28 / 38 / 48 / 58 / 68 / 78 / 88)	

DIN 1705 (EN 1982)

GC - CuSn12 (G-Bz 12)

Neue Werkstoffbezeichnung: CC 493 K (2.1052) Lagerlängen ab 1000mm

	GC - CuSn12 (G-Bz 12) CC 493 K W.-Nr. 2.1052	
Abmessung Ø [mm] Liefermaße	Abmessung Ø [mm] Lieferlängen	
51 x (19 / 24 / 29)	92 x (28 / 48 / 58)	
61 x (19 / 29 / 39)	102 x (38 / 48 / 58 / 68)	
71 x (18 / 28 / 38)	112 x (48 / 58 / 68)	
82 x (28 / 38 / 48)		

DIN 1705 (EN 1982)